

NASA/CR—2000-210221



Suspended Patch Antennas With Electromagnetically Coupled Inverted Microstrip Feed for Circular Polarization

Rainee N. Simons
Dynacs Engineering Company, Inc., Brook Park, Ohio

The NASA STI Program Office . . . in Profile

Since its founding, NASA has been dedicated to the advancement of aeronautics and space science. The NASA Scientific and Technical Information (STI) Program Office plays a key part in helping NASA maintain this important role.

The NASA STI Program Office is operated by Langley Research Center, the Lead Center for NASA's scientific and technical information. The NASA STI Program Office provides access to the NASA STI Database, the largest collection of aeronautical and space science STI in the world. The Program Office is also NASA's institutional mechanism for disseminating the results of its research and development activities. These results are published by NASA in the NASA STI Report Series, which includes the following report types:

- **TECHNICAL PUBLICATION.** Reports of completed research or a major significant phase of research that present the results of NASA programs and include extensive data or theoretical analysis. Includes compilations of significant scientific and technical data and information deemed to be of continuing reference value. NASA's counterpart of peer-reviewed formal professional papers but has less stringent limitations on manuscript length and extent of graphic presentations.
- **TECHNICAL MEMORANDUM.** Scientific and technical findings that are preliminary or of specialized interest, e.g., quick release reports, working papers, and bibliographies that contain minimal annotation. Does not contain extensive analysis.
- **CONTRACTOR REPORT.** Scientific and technical findings by NASA-sponsored contractors and grantees.

- **CONFERENCE PUBLICATION.** Collected papers from scientific and technical conferences, symposia, seminars, or other meetings sponsored or cosponsored by NASA.
- **SPECIAL PUBLICATION.** Scientific, technical, or historical information from NASA programs, projects, and missions, often concerned with subjects having substantial public interest.
- **TECHNICAL TRANSLATION.** English-language translations of foreign scientific and technical material pertinent to NASA's mission.

Specialized services that complement the STI Program Office's diverse offerings include creating custom thesauri, building customized data bases, organizing and publishing research results . . . even providing videos.

For more information about the NASA STI Program Office, see the following:

- Access the NASA STI Program Home Page at <http://www.sti.nasa.gov>
- E-mail your question via the Internet to help@sti.nasa.gov
- Fax your question to the NASA Access Help Desk at (301) 621-0134
- Telephone the NASA Access Help Desk at (301) 621-0390
- Write to:
NASA Access Help Desk
NASA Center for Aerospace Information
7121 Standard Drive
Hanover, MD 21076

NASA/CR—2000-210221



Suspended Patch Antennas With Electromagnetically Coupled Inverted Microstrip Feed for Circular Polarization

Rainee N. Simons
Dynacs Engineering Company, Inc., Brook Park, Ohio

Prepared for the
2000 International Symposium on Antennas and Propagation and
USNC/URSI National Radio Science Meeting
sponsored by the Institute of Electrical and Electronics Engineers
Salt Lake City, Utah, July 16–21, 2000

Prepared under Contract NAS3–98008

National Aeronautics and
Space Administration

Glenn Research Center

Acknowledgments

This work was performed under the task High Performance Printed Antennas and funded by the Cross Enterprise Technology Development Program (CETDP) in code SM.

This report is a preprint of a paper intended for presentation at a conference. Because of changes that may be made before formal publication, this preprint is made available with the understanding that it will not be cited or reproduced without the permission of the author.

Available from

NASA Center for Aerospace Information
7121 Standard Drive
Hanover, MD 21076
Price Code: A02

National Technical Information Service
5285 Port Royal Road
Springfield, VA 22100
Price Code: A02

SUSPENDED PATCH ANTENNAS WITH ELECTROMAGNETICALLY COUPLED INVERTED MICROSTRIP FEED FOR CIRCULAR POLARIZATION

Rainee N. Simons
Dynacs Engineering Company, Inc.
2001 Aerospace Parkway
Brook Park, Ohio 44142
Tel (216) 433-3462 Fax (216) 433-8705
E-mail: Rainee.N.Simons@grc.nasa.gov

Abstract: The paper demonstrates a suspended nearly square patch antenna with offset feed and a square patch antenna with truncated corners for circular polarization. The antennas are excited by an electromagnetically coupled inverted microstrip feed. In addition a new transition between conventional microstrip and inverted microstrip is proposed. The measured results include the axial ratio and the impedance bandwidth of the antennas.

I. INTRODUCTION

Future space borne microwave/millimeter-wave systems such as radars, radiometers and communication systems will require printed antennas which have high gain, high efficiency, low profile, light weight and low cost. Printed antenna arrays with conventional microstrip corporate feed suffer from excessive conductor loss at millimeter-wave frequencies [1], [2]. The high conductor loss reduces the gain and the efficiency of the array. In addition, the thick dielectric substrate required for bandwidth contributes substantially to the mass to the array [3]. The conductor loss can be reduced by constructing the feed network using low loss transmission media such as, inverted microstrip [1], [2], suspended microstrip [4] and suspended substrate stripline [5]. Since, the dielectric substrate in these transmission media is very thin there is considerable saving in mass also. A suspended patch antenna excited by an electromagnetically coupled inverted microstrip feed at S-Band frequency has been demonstrated in [6]. In this paper first, a suspended nearly square patch antennas with offset feed, second, a suspended square patch antenna with corners truncated for circular polarization is demonstrated. Both antennas are electromagnetically coupled to inverted microstrip feed and operate at K-Band frequencies. The advantages of the above feeding technique include significantly lower attenuation and easier fabrication due to wider strip width for a given characteristic impedance (Z_0) [7]. Third, a novel transition from conventional microstrip to inverted microstrip is demonstrated. This transition will allow fast and inexpensive characterization of the above antennas at millimeter-wave frequencies using coplanar waveguide (CPW) RF probes. The measured results include the axial ratio and the impedance bandwidth of the antennas.

II. ANTENNA CONSTRUCTION

A schematic of a suspended nearly square patch antenna electromagnetically coupled to an inverted microstrip offset feed for circular polarization is shown in Figure 1. The inverted microstrip line consists of a thin dielectric substrate (RT/duroid 5880, $\epsilon_r = 2.22$) of thickness h (0.01 inch) separated from a ground plane by an air gap of height g (0.01 inch). The strip conductor of width

W_i (≈ 0.045 inch for $Z_0 = 50 \Omega$) is situated on the lower surface of the dielectric substrate facing the ground plane. The length and width of the patch are L_1 and L_2 respectively. The feed offset and the overlap between the patch and the feed are indicated as d and S respectively in Figure 1. Next, a suspended square patch antenna ($L \times L$) with two corners truncated (ΔL) is shown in Figure 2. The feed is symmetrically located and the overlap between the patch and the feed is S .

III. MICROSTRIP-TO-INVERTED MICROSTRIP TRANSITION

A back-to-back conventional microstrip-to-inverted microstrip transition is shown in Figure 3. In this transition the strip conductors of the microstrip and the inverted microstrip overlap and power is transferred through electromagnetic coupling. A pair of coplanar waveguide (CPW) pads are provided at the microstrip input and output ports for characterization using RF probes.

IV. EXPERIMENTAL RESULTS

The measured axial ratio of the suspended nearly square patch antenna with offset fed is shown in Figure 4. The 3 dB axial ratio bandwidth is about 1.59 percent. The measured return loss of the suspended square patch antenna with truncated corners is shown in Figure 5. The -10.0 dB return loss bandwidth is about 7.0 percent. Additional measurements including radiation patterns, return loss and axial ratio of the antennas and the insertion/return loss of the transition are in progress.

V. CONCLUSIONS

The paper demonstrates a suspended nearly square patch antenna with offset feed and a suspended square patch antenna truncated corners for circular polarization. The antennas are excited by an electromagnetically coupled inverted microstrip feed and operate at K-Band frequencies. The measured results include the axial ratio and the impedance bandwidth of the antennas.

References

- [1] T. Itoh, "Overview of Quasi-Planar Transmission Lines," *IEEE Trans. Microwave Theory Tech.*, vol. 37, no. 2, pp. 275–280, February 1989.
- [2] B.E. Spielman, "Dissipation Loss Effects in Isolated and Coupled Transmission Lines," *IEEE Trans. Microwave Theory Tech.*, vol. MTT-25, no. 8, pp. 648–656, August 1977.
- [3] Data Sheet RT/duroid[®] 5880, Rogers Corporation, Chandler, Arizona.
- [4] J.M. Baracco and A. Carlstrom, "X-Band Microstrip Array Antenna in Suspended Technology," 1997 *IEEE Antennas and Propagation Society Inter. Symp. Dig.*, vol. 2, pp. 1256–1259, 1997.
- [5] E. Rammos, "A Low Tolerance Dual Slot Radiator for Space and Ground Applications," 1991 *IEEE Antennas and Propagation Society Inter. Symp. Dig.*, vol. 3, pp. 1599–1602, 1991.
- [6] Q. Zhang, Y. Fukuoka and T. Itoh, "Analysis of a Suspended Patch Antenna Excited by an Electromagnetically Coupled Inverted Microstrip Feed," *IEEE Trans. Antennas and Propagation*, vol. AP-33, no. 8, pp. 895–899, August 1985.
- [7] J. Rivera and T. Itoh, "Analysis of an Electromagnetically Coupled Patch Antenna," 1983 *IEEE Antennas and Propagation Society Inter. Symp. Dig.*, vol. 1, pp. 170–173, 1983.




Figure 1.—Schematic of a nearly square patch antenna electromagnetically coupled to an inverted microstrip line offset feed for circular polarization. Dimensions in inches are $L_1 = 0.215$, $L_2 = 0.206$, $S = 0.049$, $d = 0.011$.




Figure 2.—Schematic of a square patch antenna with corners removed and electromagnetically coupled to an inverted microstrip line feed for circular polarization. Dimensions in inches are $L = 0.207$, $\Delta L = 0.04$, $S = 0.125$.




Figure 3.—Schematic of a back-to-back conventional microstrip-to-inverted microstrip transition. $W_m = 0.03$ inches.




Figure 4.—Measured axial ratio of the nearly square patch antenna with offset feed.




Figure 5.—Measured return loss of the square patch antenna with corners removed.

REPORT DOCUMENTATION PAGE			<i>Form Approved</i> <i>OMB No. 0704-0188</i>	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE June 2000	3. REPORT TYPE AND DATES COVERED Final Contractor Report	
4. TITLE AND SUBTITLE Suspended Patch Antennas With Electromagnetically Coupled Inverted Microstrip Feed for Circular Polarization			5. FUNDING NUMBERS WU-632-6E-51-00 NAS3-98008	
6. AUTHOR(S) Rainee N. Simons				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Dynacs Engineering Company, Inc. 2001 Aerospace Parkway Brook Park, Ohio 44142			8. PERFORMING ORGANIZATION REPORT NUMBER E-12074	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) National Aeronautics and Space Administration John H. Glenn Research Center at Lewis Field Cleveland, Ohio 44135-3191			10. SPONSORING/MONITORING AGENCY REPORT NUMBER NASA CR-2000-210221	
11. SUPPLEMENTARY NOTES Prepared for the 2000 International Symposium on Antennas and Propagation and USNC/URSI National Radio Science Meeting sponsored by the Institute of Electrical and Electronics Engineers, Salt Lake City, Utah, July 16-21, 2000. Project Manager, Dennis Vano, Systems Engineering Division, NASA Glenn Research Center, organization code 7830, (216) 433-2730.				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Unclassified - Unlimited Subject Category: 33 This publication is available from the NASA Center for AeroSpace Information, (301) 621-0390.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) The paper demonstrates a suspended nearly square patch antenna with offset feed and a square patch antenna with truncated corners for circular polarization. The antennas are excited by an electromagnetically coupled inverted microstrip feed. In addition a new transition between conventional microstrip and inverted microstrip is proposed. The measured results include the axial ratio and the impedance bandwidth of the antennas.				
14. SUBJECT TERMS Suspended substrate patch; Inverted microstrip; Array antenna; Circular polarization; Suspended substrate stripline			15. NUMBER OF PAGES 10	
			16. PRICE CODE A02	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT	